Whether you're working with coaxial, extruded, or magnet/enamel wire or cable, Eraser offers a wide range of stripping options. Designed to our exacting specifications to meet your specific needs, our complete line of blade, thermal, or chemical strippers features more than 40 products. And if you can't find it here, we can custom build one for you.

Coaxial wire & cable strippers

824 Portable Coaxial Cable Stripper

This portable, two pound unit can be used to strip coaxial cables, including RGU, semi-rigid, plenum, and heliax. Unit comes with carrying case, charger and adapter cord.

Specifications

Max. cable size.....0.430" OD (10.9mmø)
Min. cable size.....0.030" OD (0.76mmø)
Max. strip length.....0.965" (24.5mm) standard, longer lengths available as special
Min. strip length.....0.050" (1.27mm) dep. on material, diameter and construction
Power.....standard battery pack 110V charger, DC adapter charger cord

Ordering information

RC2000 (824).....110V
RC2001 (824).....220/230V, European plug

See page 25 & 28 for cutter head selection and options.

1256 Coaxial Cable Stripper

This footswitch-activated bench stripper can strip up to five levels on coaxial cable in less than five seconds.

Specifications

Max. cable size.....0.430" OD (10.9mmø)
Min. cable size.....0.030" OD (0.76mmø)
Max. strip length.....1.75" (44.4mm) standard, longer lengths available as special
Min. strip length.....0.050" (1.27mm) dep. on material, diameter and construction

Ordering information

RC1071 (1256).....110V 60Hz
RC1068 (1256).....110V 60Hz, 1/4" diameter drilled for extended conductor strip length

See page 25 & 28 for cutter head selection and options.

MSS205 Coaxial Cable & Braid Stripper

SPECIAL ORDER

This stripper quickly severs braid on shielded cables and fuses to prevent fraying.

Specifications

Max. cable size.....0.370" OD (9.4mmø)
Max strip length.....infinite
Min. strip length.....1/8" (3.2mm)
Electrode size.....1-1/2" (39mm) long
May be drilled to strip more than one cable diameter at a time

Ordering information

Quoted Only (MSS205).....220/240V 50/60Hz requires 90 PSI, 1/8" pipe connector

Optional Parts

PR0003.....air filter, regulator and lubricator
PR0227.....undrilled electrodes
AR6701.....FE1 fume extractor, 115V 50/60Hz
AR6702.....FE1 fume extractor, 230V 50/60Hz
AA0004 replacement brass Eraser brush to clean electrodes