



The Eraser Company, Inc.
PO Box 4961/ 123 Oliva Drive
Syracuse, NY 13221, USA

Always Moving Forward®

Phone: (315) 454-3237
1 (800) 724-0594 (USA/Canada)
FAX: (315) 454-3090
e-mail: info@eraser.com
Website: www.eraser.com

Model MR30A Air-Operated Nipper OPERATING INSTRUCTIONS

SET-UP:

Before connecting to an air supply, install the blade set. Remove the blade pivot screw and nut. Install the blade pivot screw and nut. Tighten.

The MR30A Nipper can now be connected to a clean, dry, lubricated, regulated air supply. We recommend Eraser's Model PR0003 Combination Air Filter, Regulator and Lubricator.

SAFETY:

1. Never operate the MR30A Nipper with air pressure higher than 85 PSI.
2. Safety glasses or other suitable eye protection should be worn at all times during the use of this tool.
3. Hearing protection should be worn at all times during the use of this tool.

OPERATION:

Connect to air supply (1/4" N.P.T. Male on air line). Actuate handle to cut wire or cable. Never actuate unit without cutting material. This may cause the blade set to prematurely wear or break.

CHANGING BLADE SET:

1. Remove blade pivot screw and nut.
2. Blade set.
3. Reinstall new blade set.
4. Install blade pivot screw.

IMPORTANT: NO LIABILITY WILL BE INCURRED BY THE ERASER COMPANY FOR INJURY, DEATH, OR PROPERTY DAMAGE CAUSED BY A PRODUCT THAT HAS BEEN SET UP, OPERATED, AND/OR INSTALLED CONTRARY TO ERASER'S WRITTEN INSTRUCTION MANUAL; OR WHICH HAS BEEN SUBJECTED TO MISUSE, NEGLIGENCE, OR ACCIDENT; OR WHICH HAS BEEN REPAIRED OR ALTERED BY ANYONE OTHER THAN ERASER, OR WHICH HAS BEEN USED IN A MANNER OR FOR A PURPOSE FOR WHICH THE PRODUCT WAS NOT DESIGNED.